

ACS12

- High pressure chemical spraying
- Operates at high pressure over 6 adjustable spraying nozzles
- Rotating turbo heads for extra impact
- Chemical resistant, 316 stainless fluid end
- Electrical plugs suitable for mines (Cooper Crouse-Hinds & Appleton)
- Voltage options of 575 VAC or 480 VAC on same unit
- Chemical resistant seal compounds
- Portable cart with heavy duty non marking wheels
- Wheel Choks lock unit in place during use and stow on frame
- 12 replacement QD style spray nozzles mounted on frame
- Easy to read pressure gauge, glycerine filled
- Adjustable pressure control
- Liquid tight magnetic starter controls
- Tool box
- Custom aluminum shipping box
- Ball valve on / off spray control per nozzle



**Use
with ACL's Dynasol
EP degreaser/cleaner to clean
any Ring Gear in Minutes -
without shutting the Mill
down!**



Specifications

Pressure	2175 PSI (Max) / 1500 PSI operating over 6 spray tips
Flow	12.8 US GPM / 48 LPM (Max) / 7.1 GPM / 26.8 LPM normal operating
Electrical	460V or 600 V - 3 Phase
Electrical Cord	50 ft / 15 m
Horse Power	10
Amp Draw	13.8 Amps @ 460V / 10.8 Amps @ 600V
Operating Cycle	Continuous Duty
Nozzles	6 x 25°, 6 x 40°, 2 x turbo nozzles
Fittings	Quick Disconnect
Hose	Steel braided - 10 ft / 3 m x 6
Dimensions L x W x H	50.5" x 48" x 59" / 128 x 122 x 150 cm
Weight	1150 lbs / 522 kgs



#1, 7157 Honeyman Street
Delta BC Canada V4G 1E2
E-mail: corporate@activechemicalsltd.com

Web: www.activechemicalsltd.com
Toll Free: 1-800-663-6090
Fax: (604) 946-3901